

2 INCH PORTABLE PRINTER

LK-P12

- ☑ Compact and rugged design
- ☑ Peel - off function
- ☑ IP42 certified : protection against dust and water
- ☑ Large capacity of paper roll up to 56mm (OD)
- ☑ Adjustable paper width from 12.7 to 58mm
- ☑ Flexible connectivity including RS-232C, USB, Bluetooth or Wi-Fi(802.11b/g/n)
- ☑ Prints at 100mm per second
- ☑ Fast AC charger and long life battery



LK-P12

Product Image

FRONT



LEFT



RIGHT



Control Panel Usage



- 1 MENU
- 2 PAPER FEED
- 3 POWER
- 4 MENU SELECTION
- 5 LCD WINDOW

Specification

Model	LK-P12	
Printer Mechanism	2inch label & receipt	
Media	Receipt, Label	
Media width	12.7mm~58mm	
Media size	56mm diameter	
Media length/ Non peel mode	12.7mm~300mm / 18mm~300mm	
Resolution	203 DPI	
Print width	48mm	
Print speed	100mm/sec(Label 60mm/sec)	
Fonts	Font A, Font B, Download bitmap and true type font	
Barcode symbols	1D	UPC-A, UPC-E, EAN-8, EAN-13, EAN-128, RSS, Postnet, CODE39, CODE93, CODE128, ITF, CODABAR
	2D	PDF417, QR code, Maxicode, GS-1, Datamatrix, Aztec
Interface	Standard	RS-232(mini DIN connector), USB
	Option	Bluetooth, Wi-Fi
Driver	Windows (2000, XP, Vista, 7), Symbian OS Windows mobile(Pocket PC, 2003, 6x), Android, Windows CE 4.2/5.0/6.0, Linux, Blackberry	
Emulation	ESC/POS, ZPL, CPCL Command compatible	
Sensor	Gap, Black mark, Paper end, Peeler	
Option	Battery cradle, Car charger, Shoulder strap, Belt clip	
Battery	Hard pack 7.4V 2200mAh	
Method of charge battery	AC / DC charger	
Impact resistance	1.5M(standard)	
IP	IP42	
Environment data	Operating	-10 ~ 50 C / 10 ~ 90% RH
	Storage	-20 ~ 60 C / 10 ~ 90% RH
Feature	Dual injection, LCD, Peeler	
Dimensions	100(W)× 158(D) × 85 (H) mm	
Weight	587g (with battery)	



SEWOO TECH CO.,LTD.

28-6, Gajangsaneopdong-ro, Osan-si, Gyeonggi-do, 447-210, Korea

T. +82-31-459-8200 F. +82-31-459-8880

<http://www.miniprinter.com>